N

SCALE 1" = 50'

0 50 100

LEGEND

EX SL A	EXISTING SINGLE LUMINAIRE, 250 WATT, 240 VOLT, HPS, TYPE II DISTRIBUTION, (HADCO PROFILER PA 31) 30' POLE HEIGHT, TOTAL HEIGHT 32.5'
EX SL B	EXISTING SINGLE LUMINAIRE, 250 WATT, 240 VOLT, HPS, TYPE III DISTRIBUTION, (HADCO PROFILER PA 31) 30' POLE HEIGHT, TOTAL HEIGHT 32.5'
EX SL C	EXISTING SINGLE LUMINAIRE, 100 WATT, 240 VOLT, HPS, TYPE II DISTRIBUTION, (STERNBERG 1430 ROADWAY FIXTURE) 12' POLE HEIGHT, TOTAL HEIGHT 12.5'
PROP SL	PROPOSED SINGLE LUMINAIRE, 100 WATT, 240 VOLT, HPS, TYPE II DISTRIBUTION, (STERNBERG 1430 ROADWAY FIXTURE) 12' POLE HEIGHT, TOTAL HEIGHT 12.5'

BUILDING FRONT EXTERIOR LIGHTING FIXTURE

Lightray | 610TABZ

Job Name: _____ Job Type: _____ Quantity: _____ Comments: _____

PRODUCT DESCRIPTION

Indirect exterior lighting not only provides illumination where you want it but also highlights the building structure for a beautiful architectural effect. Our collection of up and down lighting fixtures are available in both Architectural Bronze and Brushed Aluminum. They are also available in both incandescent and LED. The fixtures are sealed with lexan lenses that are water tight and allows, for the use of constant light bulbs.



MEASUREMENTS
DIMENSION : 7" W x 5.25" D x 7.25" SH
BACK PLATE : 4.5" W x 5.5" W x 0.38" HCO
HANGING HEIGHT : 5.99 lb

LAMPING
INPUT VOLTAGE : 120V
BULB : 1 x 75W Incandescent E26 Medium , 75W Total
BULB INCLUDED : (Not Included)
DIMMABLE : Yes

FINISHES OPTION
Architectural Bronze
Brushed aluminum

MATERIAL
Aluminum

RATINGS
IP55 rating
Wet Location
DARK SKY

ADDITIONAL
INSTALL UP/DOWN: Any
OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

MAXIM LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
255 NORTH VINELAND AVE | CITY OF INDUSTRY , CA 91746
EASTERN DISTRIBUTION CENTER
4200 SHILLET DR. | ATLANTA, GA 30336
P: 626.934.4200 | F: 626.934.4225 | maxim@lighting.com

BUILDING REAR/GARAGE EXTERIOR LIGHTING FIXTURE

Diverse | 57613

Job Name: _____ Job Type: _____ Quantity: _____ Comments: _____

- Slim design makes it a great substitute for recessed lighting
- Fully dimmable with C-Tran Dimmers
- High powered LEDs create a brighter shine
- Approved for use in closets and storage spaces
- Reduces energy consumption and operating costs by up to 80% over incandescent downlights
- Suitable for wet locations
- Innovative design runs cooler to maximize energy efficiency
- Reflector cup and diffuser create brighter shine
- Energy Star Certified, CRI 90+
- ETL/ LEDS, IP65
- Directly installs in any 3" or 4" junction box

PRODUCT DESCRIPTION

The very compact LED flush mount directly installs on any 3" or 4" junction box and gives the look of a recessed trim. Available in Black, Bronze and Brushed Aluminum. The Diverse luminaire is dimmable and also approved for wet or damp locations so it can be used in virtually any ceiling application, including showers.

MEASUREMENTS
DIMENSION : 7.5" L x 7.5" W x 1.25" H
HANGING WEIGHT : 0.4 lb

LAMPING
INPUT VOLTAGE : 120V
LUMENS : 1,200 Rated (950 Det.)
BULB : 15.5W LED PCB Integrated , 149W Total
BULB INCLUDED : (Not Included)
DIMMABLE : Yes, CL
CRI : 90 CRI
COLOR_TEMP : 3000K

FINISHES OPTION
Black
Bronze
Satin Nickel
White

GLASS
White MT

MATERIAL
Aluminum + Polycarbonate

RATINGS
ETLus
Wet Location
Energy Star

ADDITIONAL
RATED LIFE 50000 Hours
OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

MAXIM LIGHTING

WESTERN DISTRIBUTION CENTER (HEADQUARTER)
255 NORTH VINELAND AVE | CITY OF INDUSTRY , CA 91746
EASTERN DISTRIBUTION CENTER
4200 SHILLET DR. | ATLANTA, GA 30336
P: 626.934.4200 | F: 626.934.4225 | maxim@lighting.com

HOLOPHANE

Job Name: | Job Location: | Quote No: | Type:

Catalog Number:
GBLP3 P80 40K MVOLT ABV QSM BK STG 20IN 1A TN BK BADF QSM BK SLA **15** SLS SB G12 BK ABS ASSETWELD



Ordering Information

Luminaire	Area/Mounting Bracket	Pole
Catalog Number: GBLP3 P80 40K MVOLT ABV **Series:** GBLP3 Gatehouse Luminaire LED Board **Lumen Package:** P80: P80 Lumen Package **Color Temperature:** 40K: 4000K **Voltage:** MVOLT: 120-277V **Optics:** ABV: Asymmetric **Mounting Method:** QSMB: Quick stem mount **Finish:** BK: Black	**Catalog Number:** STG 20IN 1A TN BK **Series:** STG: Straight Crossarm with **Straight Length:** 20IN: 20IN **Number of Arms:** 1A: Single arm **Pole Orientation:** TN: Tenon mount **Finish:** BK: Black	**Catalog Number:** SLA **15** SLS SB G12 BK **Series:** SLA: Slip Lid **Pole Height:** **15ft 15 FT** **Shaft Size:** SLS: Shaft Stem 3.25IN Tubular Steel **Shaft Finish:** SB: Satin Bronze **Finish:** BK: Black **Pole Top Mounting:** G12: G1 x 12 tenon **Finish:** BK: Black **Base Mounting (ABS):** Anchor bolt (specified ship)

Anchor Bolt	Anchor bolt template
Catalog Number: AB-27-4 **Anchor Bolt:** (AB-27-4): (27-2 x	**Catalog Number:** TMP8017 **Anchor Bolt Template Number:** (TMP8017): (8"PINOT)

Mackie Consultants, LLC
9575 W. Higgins Road, Suite 500
Rosemont, IL 60018
(847)696-1400
www.mackieconsult.com
MACKIE CONSULTANTS

CLIENT:
D·R·HORTON® America's Builder
D.R. HORTON, INC.-MIDWEST
1750 E. GOLF ROAD, SUITE 925
SCHAUMBURG, ILLINOIS 60173

DATE	DESCRIPTION OF REVISION	BY
06/20/2025	REVISED PER VILLAGE COMMENTS	RJM
06/12/2025	REVISED PER VILLAGE COMMENTS	AA

DESIGNED	JJD
DRAWN	JJD
APPROVED	KJM
DATE	03/14/2025
SCALE	1" = 50'

PHOTOMETRIC PLAN
CANTERA POINT
WARRENVILLE, ILLINOIS

SHEET 1 OF 1

PROJECT NUMBER: 4821

© MACKIE CONSULTANTS LLC, 2025

ILLINOIS FIRM LICENSE 184-002694

6/20/2025 1:02:14 PM
N:\4821\Engineering\Design\Photometrics\Cantera Point - Photometric Plan.pdf